

# 2024 RENEGADE X MR 650



 Catalyst Gray & Neo Yellow

<b>ENGINE</b>		<b>650</b>
Type	62 hp, Rotax® 650 cc V-twin, snorkeled, liquid-cooled	
Fuel Delivery System	Intelligent Throttle Control (ITC™) with Electronic Fuel Injection (EFI)	
Transmission	CVT L / H / N / R / P	
Drive Train	Selectable 2WD / 4WD / Lock 4WD with Visco-4Lok <sup>†</sup> front differential	
Driving Assistance	Work / Standard / Sport modes Intelligent Engine Braking (iEB™)	
Power Steering	Tri-Mode Dynamic Power Steering (DPS™)	
<b>SUSPENSIONS</b>		
Front Suspension	Arched double A-arm with front sway bar	
Front Shocks	SHOWA gas shock	
Rear Suspension	Torsional Trailing arm Independent (TTI)	
Rear Shocks	SHOWA gas shock	
<b>TIRES &amp; WHEELS</b>		
Front / Rear Tires	ITP <sup>†</sup> Mega Mayhem <sup>†</sup> 28 x 8 / 10 x 12 in.	
Wheels	12 in. cast-aluminum beadlock	
<b>BRAKES</b>		
Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers	
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper	

## PACKAGE HIGHLIGHTS

- Rotax® snorkeled V-Twin engine with relocated CVT intake and outlet
- Tri-Mode Dynamic Power Steering (DPS™)
- Visco-4Lok<sup>†</sup> auto-locking front differential
- 28 in. ITP<sup>†</sup> Mega Mayhem<sup>†</sup> tires with 12 in. aluminum beadlock wheels
- Heavy-duty front and rear bumpers
- Aluminum taper-profile handlebar with grab handle and full wrap handguards
- Front & central aluminum skid plate
- X-package coloration, graphics and seat cover

## DIMENSIONS & CAPACITIES

Estimated Dry Weight*	870 lb (395 kg)
L x W x H	83 x 50 x 56 in. (224 x 127 x 131 cm)
Wheelbase	51 in. (129.5 cm)
Ground Clearance	12 in. (30.5 cm)
Seat Height	35.3 in. (89.5 cm)
Rack Capacity	Rear: 35 lb (16 kg)
Storage Capacity	N/A
Towing Capacity	1,300 lb (590 kg)
Fuel Capacity	5.4 gal (20.5 L)

## FEATURES

Gauge	4.5 in. digital display
Instrumentation	DC outlet, 15 A connector
Ignition	RF Digitally Encoded Security System (D.E.S.S.™) with cord
Lighting	LED headlights
Winch	Prewired for available winch
Seat	Standard
Handlebar	Aluminum taper-profile handlebar with grab handle and full wrap handguards
Protection	Front and rear bumpers Mudguards Front and central aluminum skid plate

## WARRANTY & EXTENDED SERVICE

Factory Warranty	6-month BRP limited warranty
Extended Service	B.E.S.T. term available up to 36 months
Terms	

# can-am®

© 2023 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are registered trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. \*Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrives GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at any time to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in the U.S.A. call the ATV Safety Institute at 1-800-887-2887. In Canada, call the Canadian Safety Council at 1-613-739-1535, ext 227. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding, alcohol and drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90 cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

